



# BEARINGS IMPORTED AND EXPORTED CO.,LTD.



12 mm x 28 mm x 8 mm SKF 6001-2Z deep groove ball bearings

Bearing No. 6001-2Z

6001-2Z Bearing 2D drawings and 3D CAD models

Size	12x28x8 mm
Bore Diameter	12 mm
Outer Diameter	28 mm
Width	8 mm
d	12 mm
D	28 mm
B	8 mm
C	8 mm
d1	17 mm
d2	– mm
r1 min.	14 mm
r2 min.	14 mm
D1	24,8 mm
D2	0,3 mm
da min.	16,9 mm
Da max.	26 mm
ra max.	0,3 mm
Weight	0,022 Kg
Basic dynamic load rating (C)	5,4 kN
Basic static load rating (C0)	2,36 kN
Fatigue load limit (Pu)	0,1
Reference speed	60000 r/min
Limiting speed	30000 r/min
Calculation factor (f0)	13
Category	Single Row Ball Bearings



## BEARINGS IMPORTED AND EXPORTED CO.,LTD.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.022
EAN	7316577758637
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	12MM Bore; 28MM Outside Diameter; 8MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	6001-2Z
Weight / LBS	0.053
Bore	0.472 Inch   12 Millimeter



## BEARINGS IMPORTED AND EXPORTED CO.,LTD.

Outside Diameter	1.102 Inch   28 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.315 Inch   8 Millimeter
$d_1$	17 mm
$D_2$	24.72 mm
$r_{1,2}$ min.	0.3 mm
$d_a$ min.	14 mm
$d_a$ max.	16.9 mm
$D_a$ max.	26 mm
$r_a$ max.	0.3 mm
Basic dynamic load rating C	5.4 kN
Basic static load rating $C_0$	2.36 kN
Fatigue load limit $P_u$	0.1 kN
Calculation factor $k_r$	0.025
Calculation factor $f_0$	13
Mass bearing	0.022 kg