



15 mm x 28 mm x 7 mm NACHI 6902 deep groove ball bearings

Bearing No. 6902

6902 Bearing 2D drawings and 3D CAD models

Size	15x28x7 mm
Bore Diameter	15 mm
Outer Diameter	28 mm
Width	7 mm
d	15 mm
D	28 mm
B	7 mm
C	7 mm
r min.	0.3 mm
da min.	17 mm
Da max.	26 mm
ra max.	0.3 mm
Weight	0.016 Kg
Basic dynamic load rating (C)	4,3 kN
Basic static load rating (C0)	2,25 kN
(Grease) Lubrication Speed	26000 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0.018
EAN	4991893811612
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0



BEARINGS IMPORTED AND EXPORTED CO.,LTD.

Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	15MM Bore; 28MM Outside Diameter; 7MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.nachi.com
Manufacturer Item Number	6902 BNLS
Weight / LBS	0.04
Bore	0.591 Inch 15 Millimeter
Outer Race Width	0.276 Inch 7 Millimeter
Outside Diameter	1.102 Inch 28 Millimeter
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	15 mm
Width	7 mm
Fillet Radius/Chamfer	0.3 mm
Dynamic Load Rating	4,300 N
Static Load Rating	2,250 N
Limiting Speed - Grease	26,000 rpm
Limiting Speed - Oil	31,000 rpm



BEARINGS IMPORTED AND EXPORTED CO.,LTD.

Factor fo	14.3
Radial Clearance	0.003 to 0.018 mm
da (min)	17 mm
Da (max)	26 mm
ra (max)	0.3 mm