



BEARINGS IMPORTED AND EXPORTED CO.,LTD.



6032Z Bearing 2D drawings and 3D CAD models

160,000 mm x 240,000 mm x 38,000 mm NTN
6032Z deep groove ball bearings

Bearing No. 6032Z

Size	160x240x38 mm
Bore Diameter	160,000 mm
Outer Diameter	240,000 mm
Width	38,000 mm
d	160,000 mm
D	240,000 mm
B	38,000 mm
C	38,000 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	5.2
EAN	4547359338737
Product Group	B00308
Enclosure	1 Metal Shield
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	160MM Bore; 240MM



BEARINGS IMPORTED AND EXPORTED CO.,LTD.

	Outside Diameter; 38MM Outer Race Width; 1 Metal Shield; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Ste
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	6032Z
Weight / LBS	13.4922
Inner Race Width	0 Inch 0 Millimeter
Bore	6.299 Inch 160 Millimeter
Outside Diameter	9.449 Inch 240 Millimeter
Outer Race Width	1.496 Inch 38 Millimeter
bore diameter:	160 mm
finish/coating:	Uncoated
outside diameter:	240 mm
bearing material:	High Carbon Chrome Steel
overall width:	38 mm
cage material:	Steel
bore type:	Round
inner ring width:	38 mm
closure type:	Single Shield
outer ring width:	38 mm
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	2800 rpm
snap ring included:	Without Snap Ring



BEARINGS IMPORTED AND EXPORTED CO.,LTD.

maximum rpm (oil):	3200 rpm
internal clearance:	CN
fillet radius:	2.1 mm
operating temperature range:	-40 to 120 ° C
maximum rpm:	3000 RPM
dynamic load capacity:	126000 N
series:	60
static load capacity:	126000 N
manufacturer product page:	Click here
precision rating:	ISO Class 0