



**180 mm x 380 mm x 75 mm NTN NU336
cylindrical roller bearings**

Bearing No. NU336

NU336 Bearing 2D drawings and 3D CAD models

Size	180x380x75 mm
Bore Diameter	180 mm
Outer Diameter	380 mm
Width	75 mm
d	180 mm
Fw	232 mm
D	380 mm
B	75 mm
C	75 mm
r min.	4 mm
r1 min.	4 mm
Weight	44,2 Kg
Basic dynamic load rating (C)	905 kN
Basic static load rating (C0)	1 150 kN
(Grease) Lubrication Speed	1 700 r/min
Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	42.44
EAN	4547359148220
Product Group	B04144
Bore Profile	Straight
Cage Material	Steel
Precision Class	RBEC 1 ISO P0



BEARINGS IMPORTED AND EXPORTED CO.,LTD.

Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	Plain Inner Ring 2 Rib Outer Ring Cage On Outer Ring ID
Long Description	180MM Bore; Straight Bore Profile; 380MM Outside Diameter; 75MM Width; Steel Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C0-Medium Int
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	NU336
Weight / LBS	93.483
Bore	7.087 Inch 180 Millimeter
Outside Diameter	14.961 Inch 380 Millimeter
Width	2.953 Inch 75 Millimeter
bore diameter:	180 mm
static load capacity:	1150000 N
outside diameter:	380 mm



BEARINGS IMPORTED AND EXPORTED CO.,LTD.

precision rating:	ISO Class 0
overall width:	75 mm
maximum rpm:	2000 rpm
flanges:	(2) Outer Ring
bearing material:	Hardened Alloy Steel
bore type:	Straight
cage material:	High Strength, 2 piece, Machined Brass
number of rows:	1
finish/coating:	Uncoated
internal clearance:	CN
closure type:	Open
ring separation:	Separable Inner Ring
fillet radius:	3 mm
operating temperature range:	-40 to 120 ° C
manufacturer product page:	Click here
dynamic load capacity:	905000 N