



50,000 mm x 110,000 mm x 27,000 mm NTN
6310LLUNR deep groove ball bearings

Bearing No. 6310LLUNR

6310LLUNR Bearing 2D drawings and 3D CAD models

Size	50x110x27 mm
Bore Diameter	50,000 mm
Outer Diameter	110,000 mm
Width	27,000 mm
d	50,000 mm
D	110,000 mm
B	27,000 mm
C	27,000 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359664614
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric



BEARINGS IMPORTED AND EXPORTED CO.,LTD.

Long Description	50MM Bore; 110MM Outside Diameter; 27MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal With Snap Ring -20 To 120 Deg C
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	6310LLUNR
Weight / LBS	2.36
Outside Diameter	4.331 Inch 110 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Bore	1.969 Inch 50 Millimeter
Outer Race Width	1.063 Inch 27 Millimeter
bore diameter:	50 mm
static load capacity:	38500 N
outside diameter:	110 mm
precision rating:	ISO Class 0
overall width:	27 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Sealed
cage material:	Steel



BEARINGS IMPORTED AND EXPORTED CO.,LTD.

row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	27 mm
snap ring included:	With Snap Ring
outer ring width:	27 mm
internal clearance:	CN
maximum rpm (grease):	4200 rpm
operating temperature range:	-40 to 120 ° C
fillet radius:	2 mm
dynamic load capacity:	62000 N
manufacturer product page:	Click here